

SERTIFIKAT O KONTROLISANJU INSPECTION CERTIFICATE

Broj / Number: C 2109

Strana / Page: 1/3

Na zahtev naručioca /
By the request of purchaser:

HL Hutterer & Lechner GmbH, 2325 Himberg, Brauhausgasse
3-5, Austria

preduzeto je/
set to:

kontrolisanje novog proizvoda / the new product inspection

u vezi sa izveštajem /

Fraunhofer IBP P-BA 233/2010, 221-1/2008,
191/2016

in relation to Inspection report.

sa priloženim dokumentima /
with attached documents:

- Izvod iz prospekt proizvoda /
Catalogue pages of product ;

INSTITUT "MIHAJLO PUPIN" - CENTAR ZA GASNU TEHNIKU izjavljuje da:
INSTITUTE "MIHAJLO PUPIN" - GAS TECHNIQUE CENTRE declares that:

predmet kontrolisanja /
the inspection object :

PODORAVNI TUŠEVI /
BARRIERE FREE SHOWERS

proizvođač /
manufacturer:

HL Hutterer & Lechner GmbH, 2325 Himberg, Brauhausgasse
3-5, Austria

oznaka modela /
mark of the model :

HL50 (W, F, FF, FU, FV, WF, WU), HL 53, HL531, HL540,
HL 541

kako je specificirano u Prilogu A, zadovoljava zahteve navedene u /
as specified in the Annex A, meets the requirements described in:

referentnom dokumentu /
reference document :

SRPS EN 1253-1:2016

Nadzor usaglašenosti predmeta kontrolisanja se obezbeđuje sa
periodičnim kontrolisanjem do dana /
Surveillance of the inspection object compliance is assured by periodical
inspection until the date :

26.05.2026. god.

izdat od / issued by :

RUKOVODILAC CENTRA ZA GASNU TEHNIKU
GAS TECHNIQUE CENTRE MANAGER

Kristina Petković, dipl. maš. inž.

Ime, Prezime / Name, Surname

mesto, datum / place, date

Beograd, 26.05.2021. god.



SERTIFIKAT O KONTROLISANJU INSPECTION CERTIFICATE

Broj / Number: C 2109

Strana / Page: 2/3

Prilog A / Annex A

Pregled proizvoda u okviru modela / Product review of the model

oznaka modela / mark of the model:	dimenzije* / dimensions: d _s (mm)	težina / weight: (g)	kratak opis / short description:
HL50 (W, F, FF, FU, FV, WF, WU)	DN 50	2261 - 9870	– tuš-kanalica za ugradnju u prostor (F), za ugradnju u prostor - pločica (FF), za ugradnju u prostor - ultra pločica (FU), za ugradnju do zida (W), za ugradnju do zida - pločica ugradnja (WF), za ugradnju do zida - ultra pločica (WU), za ugradnju u površinu sa vertikalnim odvodom (FV),/ <i>shower channel for in-space installation (F), for in-space installation - superficial (FF), for in-space installation - extra superficial (FU), for wall-connected installation (W), for wall-connected superficial installation (WF), for wall-connected installation - extra superficial (WU), for in-space installation with vertical drainage,</i> – izrađeni INOX 1.14301/PP (polipropilen),/ <i>made of INOX 1.4310/PP(polypropylene),</i> – kapacitet - u zavisnosti od dužine tuš kanalice, vrednost data u katalogu proizvoda,/ <i>capacity - according to the length of shower channel, values given in catalogue pages,</i> – zvučno-izolovane nožice za tačno podešavanje visine tuš kanalice./<i>soundproofing legs for accurate setting of shower channel height.</i>
HL53 (K,KF)	DN 40 DN50	1250- 2950	– tuš kanalica/ <i>shower channel</i> – izrađeni PP (polipropilen)/ <i>made of PP(polypropylene),</i> – kapacitet - u zavisnosti od dužine tuš kanalice, vrednost data u katalogu proizvoda,/ <i>capacity - according to the length of shower channel, values given in catalogue pages</i>
HL540	DN 50	1533 - 1898	– tuš slivnik sa minimalnom ugradnom visinom od 80 mm horizontalnim odvodom i sifonom PRIMUS (sprečava prodor neprijatnih mirisa i bez vode u sifonu),/ <i>shower drain with 80 mm minimum built-in height, horizontal drainage, and PRIMUS siphon (blockage of awkward odor break-through from sewage system pipes in environment, without water in siphon)</i> – izrađeni INOX/PP (polipropilen)/ <i>made of INOX/PP(polypropylene),</i> – podesiva ugradna visina (8-20 cm),/ <i>adjustable in-built height (8-20 cm),</i> – kapacitet - 0,8 l/s./ <i>capacity - 0,8 l/s.</i>
HL541	DN40/50	-	– tuš slivnik sa minimalnom ugradnom visinom od 65 mm/ <i>shower drain with 65 mm minimum built-in height,</i> – izrađeni INOX/PP (polipropilen)/ <i>made of INOX/PP(polypropylene),</i> – klasa nosivosti: K3 - 300 kg./<i>load class: K3 - 300 kg.</i>

* - dimenzija izlaznog priključka / *dimension of outlet socket*

Sertifikat o kontrolisanju
Inspection certificate

SERTIFIKAT O KONTROLISANJU

INSPECTION CERTIFICATE

Broj / Number: C 2109

Strana / Page: 3/3

oznaka modela / mark of the model:	dimenzije* / dimensions: d _s (mm)	težina / weight: (g)	kratak opis / short description:
HL531	DN 50	2178 - 2890	- tuš-kanalica „PRIMUS-LINE” sa ugradnim EPS elementom, INOX-okvirom i rešetkom, ugradna visina 79 mm, horizontalni odvod i sifonom PRIMUS (sprečava prodor neprijatnih mirisa i bez vode u sifonu),/ <i>shower channel „PRIMUS-LINE” with built-in EPS element, INOX-frame and screen, and 79 mm built-in height, horizontal drainage and PRIMUS siphon (blockage of awkward odor break-through from sewage system pipes in enviroment, without water in siphon),</i> - izrađeni PP/ABS/EPS-40/INOX V2A,/ <i>made of PP/ABS/EPS-40/INOX V2A,</i> - kapacitet - 0,6 l/s./ <i>capacity - 0,6 l/s.</i>

* - dimenzija izlaznog priključka / *dimension of outlet socket*

Inspection certificate

Sertifikat o kontrolisanju